

Key Features

- **Ultimate Precision:** 100% Adobe RGB & 98% DCI-P3 with True 10-bit Color
- **Perfect From Screen to Print :** Fogra and G7 Certification as print-out quality guarantee for flawless soft proofing.
- **Maximum Palette Power:** Our exclusive ColorPro Sense leverages the Pantone system and empowers you to detect and choose hues to find a perfect match, even offering multiple suggestions.
- **Instant Color Adjustment:** Our exclusive ColorPro Wheel puts color calibration and adjustments at your fingertips with Adobe Software and on-screen displays
- **Portable Darkroom:** Foldaway hood attaches instantly to eliminate ambient light when you need to "go dark"



Product Description

Artists render fleeting moments of beauty by their vision. Now there's a color monitor that delivers on printing that vision with unparalleled color adjustment and soft-proofing technology. With 100% Adobe RGB & 98% DCI-P3, True 10bit Color and Fogra and G7 Certification, the quality of your color is guaranteed. You may choose to broaden your palette with multiple suggestions, courtesy of ColorPro Sense. Or fine tune your vision with fingertip control using the ColorPro Wheel for calibration and adjustment. See it, dream it and print your vision. Beauty in the Mundane.

Visit Us  www.viewsonic.com

DISPLAY		POWER		GENERAL	
Display Size (in.):	27	Eco Mode (Conserve):	45W	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, CCC, China RoHS, China Energy Label, CECP
Viewable Area (in.):	27	Eco Mode (optimized):	55W		
Panel Type:	IPS Technology	Consumption (typical):	67W		
Resolution:	3840 x 2160	Consumption (max):	70W	PACKAGE CONTENTS:	VP2786-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, USB Type-C Cable (Male-Male) x1, Quick Start Guide x1, Hood x1, ColorPro Wheel x1
Resolution Type:	UHD (Ultra HD)	Voltage:	AC 100-240V		
Static Contrast Ratio:	1,300:1 (typ)	Stand-by:	0.5W		
Dynamic Contrast Ratio:	20M:1	Power Supply:	Internal Power Supply	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Light Source:	LED	ADDITIONAL HARDWARE		Warranty:	*Warranty offered may differ from market to market
Brightness:	350 cd/m ² (typ)	Kensington Lock Slot:	1	Power Management:	Energy Star standards, EPEAT
Colors:	1.07B	Cable Organization:	Yes		
Color Space Support:	10 bit true	CONTROLS			
Aspect Ratio:	16.9	Physical Controls:	Joystick key: Up, Right, Down, Left, Center; Power		
Response Time (Typical GTG):	5ms	On Screen Display:	Input Select, Color Model, ViewMode, Audio Adjust, Setup Menu		
Response Time (GTG w/OD):	5ms	OPERATING CONDITIONS			
Viewing Angles:	178° horizontal, 178° vertical	Temperature:	32°F to 104°F (0°C to 40°C)		
Backlight Life (Hours):	30000 Hrs (Min)	Humidity (non-condensing):	20% to 90%		
Curvature:	Flat	WALL MOUNT			
Refresh Rate (Hz):	60	VESA Compatible:	100 x 100 mm		
Blue Light Filter:	Yes	INPUT SIGNAL			
Flicker-Free:	Yes	Frequency Horizontal:	15 ~ 204KHz		
Color Gamut:	Adobe RGB: 113% size / 100% coverage (Typ)	Frequency Vertical:	24 ~ 120Hz		
	DCI-P3: 112% size / 98% coverage (Typ)	VIDEO INPUT			
	EBU: 151% size / 100% coverage (Typ)	Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C		
	REC709: 152% size / 100% coverage (Typ)	ERGONOMICS			
	SMPTE-C: 165% size / 100% coverage (Typ)	Height Adjust (mm):	130		
	NTSC: 108% size (Typ)	Swivel:	120°		
sRGB: 152% size / 100% coverage (Typ)	Tilt (Forward/Back):	-3° / 21°			
Pixel Size:	0.155 mm (H) x 0.155 mm (V)	Pivot (Right/Left):	90° / 90°		
Surface Treatment:	Anti-Glare, Hard Coating (3H)	WEIGHT (IMPERIAL)			
COMPATIBILITY		Net (lbs):	18.4		
PC Resolution (max):	3840x2160	Net Without Stand (lbs):	10.8		
Mac® Resolution (max):	3840x2160	Gross (lbs):	29		
PC Operating System:	Windows 10/11 certified; macOS tested	WEIGHT (METRIC)			
Mac® Resolution (min):	3840x2160	Net (kg):	8.3		
CONNECTOR		Net Without Stand (kg):	4.9		
USB 3.2 Type A Down Stream:	4	Gross (kg):	13.2		
USB 3.2 Type B Up Stream:	1	DIMENSIONS (IMPERIAL) (WXHxD)			
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1	Packaging (in.):	27.2 x 19.9 x 8.9		
Micro USB:	1	Physical (in.):	24.1 x 17.68~22.41 x 9.1		
3.5mm Audio Out:	1	Physical Without Stand (in.):	24.1 x 14.1 x 2.2		
HDMI 2.0 (with HDCP 2.2):	2	DIMENSIONS (METRIC) (WXHxD)			
DisplayPort:	1	Packaging (mm):	692 x 505 x 225		
Power in:	3-pin Socket (IEC C14 / CEE22)	Physical (mm):	613 x 449.11~569.11 x 232		
		Physical Without Stand (mm):	613 x 358 x 55		