

## Be Your Window To The World

Als idealer Monitor für professionelle Anwendungen vereint der MSI Modern MD271PWDE ein schlichtes und modernes Design mit optimaler Bildqualität. Dank der 27 Zoll großen Bildschirmdiagonale und FHD-Auflösung (1920x1080) behältst du stets den Überblick - egal ob du Bilder und andere Medien bearbeitest oder alltägliche Office-Aufgaben erledigst. Das IPS-Panel bietet eine brillante Farbdarstellung, optimale Helligkeitswerte und eine hohe Blickwinkelstabilität. Vielfältige Anschlussmöglichkeiten erlauben es, mühelos mehrere Geräte am Bildschirm zu betreiben. Dank praktischen USB-Typ-C Anschluss ist der Monitor auch für die Zukunft gerüstet.



### Selling Points

- IPS-Panel für ideale Bildschirmfarben und Helligkeit
- Augenschonend dank der TÜV-zertifizierten Anti Flicker- und Less Blue Light-Technologien
- Ergonomischer Standfuß: Durch Neigen, Schwenken und Höhenverstellung lässt sich der Monitor optimal an die individuelle Sitzhaltung anpassen
- Das 75 Hz-Display zeigt mehr Bilder pro Sekunde und sorgt so für ein angenehmes Seherlebnis
- Umfangreiche Anschlussmöglichkeiten: HDMI-, USB Typ-C und Displayport-Eingänge bieten den passenden Anschluss für deine Geräte und erleichtern die Arbeit mit mehreren Geräten
- Einfacher Aufbau: Der Monitor lässt sich kinderleicht zusammenbauen und mit VESA-Halterung mühelos an Wände und Halterungen montieren
- Integrierte Lautsprecher
- Gewinner des Red Dot Design Awards 2021



Bilder und Logos: [Produktanlage Modern MD271PWDE](#)



1. 1x USB Typ C
2. 1x HDMI (1.4)
3. 1x Kopfhörer Ausgang
4. 1x DC Jack

## Spezifikationen

<b>SKU Number</b>	9S6-3PA4FH-045
<b>Entity MKT Name</b>	Modern MD271PWDE
<b>Local Dimming</b>	NA
<b>Screen Size</b>	27" (69 cm)
<b>Active Display Area (mm)</b>	597.888(H) X 336.312(V)
<b>Curvature</b>	Flat
<b>Panel Type</b>	IPS
<b>Resolution</b>	1920x1080 (FHD)
<b>Pixel pitch</b>	0.3114(H)X0.3114(V)
<b>Aspect Ratio</b>	16:9
<b>Dynamic Refresh Rate technology</b>	NA
<b>Activated Range</b>	NA
<b>HDR (High dynamic range)</b>	NA
<b>SDR Brightness (nits)</b>	250
<b>Contrast Ratio</b>	1000:1
<b>DCR (Dynamic Contrast Ratio)</b>	100000:1
<b>Signal Frequency</b>	30~112 KHz(H) / 48~75 Hz(V)
<b>Refresh Rate</b>	75Hz
<b>Response Time (MPRT)</b>	NA
<b>Response Time (GTG)</b>	5ms
<b>Response Time (Tr + Tf)</b>	14ms
<b>View Angles</b>	178°(H)/178°(V)
<b>NTSC (CIE1976 area percentageoverlap)</b>	91.25%/78.60%
<b>NTSC (CIE1931 area percentageoverlap)</b>	73.78%/70.40%
<b>sRGB (CIE1976 area percentageoverlap)</b>	104.61%/96.90%
<b>sRGB (CIE1931 area percentageoverlap)</b>	104.17%/95.60%
<b>Adobe RGB (CIE1976 area percentageoverlap)</b>	89.57%/84.40%
<b>Adobe RGB (CIE1931 area percentageoverlap)</b>	77.22%/73.90%
<b>DCI-P3 (CIE1976 area percentageoverlap)</b>	83.41%/82.10%
<b>DCI-P3 (CIE1931 area percentageoverlap)</b>	76.79%/76.50%
<b>Rec.709 (CIE1976 area percentageoverlap)</b>	NA
<b>Rec.709 (CIE1931 area percentageoverlap)</b>	NA
<b>Surface Treatment</b>	Anti-glare
<b>Display Colors</b>	16.7M
<b>Color bit</b>	8 bits
<b>Note_DP</b>	NA
<b>Note_HDMI</b>	1920 x 1080 (Up to 75Hz)
<b>Note_DVI</b>	N/A
<b>HDMI</b>	1
<b>HDMI version</b>	1.4
<b>HDMI HDCP version</b>	1.4
<b>DisplayPort</b>	NA
<b>DisplayPort version</b>	NA
<b>DisplayPort HDCP version</b>	NA
<b>Thunderbolt version</b>	NA
<b>Thunderbolt HDCP version</b>	NA
<b>USB Type C (DisplayPort Alternate)</b>	1
<b>DVI</b>	NA
<b>D-Sub</b>	NA
<b>Mic-in</b>	NA
<b>Mic-in upstream</b>	NA
<b>Headphone-out</b>	1
<b>Audio Combo</b>	NA
<b>USB 2.0 Type B</b>	NA
<b>USB 3.2 Gen 1 Type B</b>	NA
<b>Lock type</b>	Kensington Lock
<b>Power Type</b>	External Adaptor 19V 3.42A
<b>Power Input</b>	100~240V, 50/60Hz
<b>Adapter's KC safety Number</b>	NA
<b>Power Cord Type</b>	C13
<b>QC Output</b>	NA
<b>QC Output Power</b>	NA
<b>PD Output</b>	NA



BUSINESS PRODUCTIVITY MONITOR

## Modern MD271PW

MODERN MD271PWDE

PD Output Power	NA
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Height)	0 ~ 110 mm
Adjustment (Pivot)	-90° ~ 90°
VESA Mounting	75x75mm
Frameless Design	Yes
Outer Carton Dimension (WxDxH) (mm)	893 x 167 x 464
Outer Carton Dimension (WxDxH) (inch)	35.16 x 6.57 x 18.27
Product Dimension with Stand (WxDxH) (mm)	613 x 200 x 401
Product Dimension with Stand (WxDxH) (inch)	24.13 x 7.87 x 15.79
Product Dimension without Stand (WxDxH) (mm)	613 x 72 x 362
Product Dimension without Stand (WxDxH) (inch)	24.13 x 2.83 x 14.25
USB 3.2 Gen 2x2 Type C	NA
USB 3.2 Gen 2x2 Type A	NA
USB 3.2 Gen 1 Type C	NA
USB 3.2 Gen 1 Type A	NA
USB 2.0 Type A	NA
USB 2.0 Type C	NA
Thunderbolt	NA
Card Reader	NA
Stand Dimension (WxDxH) (mm)	230 x 200 x 415
Stand Dimension (WxDxH) (inch)	9.06 x 7.87 x 16.34
Weight (Net lbs)	12.35
Weight (Gross lbs)	18.61
Certification	全球(WW)/CB EU(歐洲)/CE-LVD DE(德國)/CE-EMC NALA(美國)/FCC DOC TW(台灣)/BSMI AU(澳大利亞)/RCM/MEPS JP(日本)/PSE,VCCI CCC
Inside Carton Dimension (WxDxH) (mm)	883 x 157 x 442
Inside Carton Dimension (WxDxH) (inch)	34.76 x 6.18 x 17.4
Weight (Net kg)	5.6
Weight (Gross kg)	8.44
DisplayPort Cable	0
HDMI Cable	1
DVI Cable	0
USB Type A to Type B Cable	0
USB Type C to Type A Cable	0
USB Type C to Type C Cable	0
Thunderbolt Cable	0
VGA Cable	0
3.5mm audio Cable	0
3.5mm combo audio Cable	0
Warranty	36 Monate Pick Up & Return
AC Adaptor	1
Power Cord	1
Warranty Card	1
Quick Guide	1
EAN	4719072817671