


# Professionelles 4K-Display mit Infrarot-Touch-Technologie

## SQ1-IR Serie

Fortschrittliche professionelle Funktionen (z. B. SDM-Slot) sowie ein elegantes, schlankes und leichtes Design, das jegliche Installationen erleichtert. Ideale Lösung zur Einrichtung gemeinschaftlicher Arbeitsumgebungen.



## KEY FEATURES

- 98" und 86", 500 cd/m<sup>2</sup>, 24/7-Betrieb, 4K IPS-Panel und blendfreie Oberfläche
- Integrierte Infrarot-Touch-Technologie mit 20 Berührungspunkten für einfache Bedienung und optimale Interaktivität
- Neuer Intel® SDM (Smart Display Module) Slot für Intel® CPU oder Schnittstellen wie SDI, NDI oder VoIP zur einfachen Integration und Installation
- Integrierter 4K USB-Media-Player: erfordert keine externen Geräte und erlaubt Updates auf USB-Speichergeräte über LAN
- Einfaches Setup mit 4K Daisy Chain und Digital Link, praktischer Sicherheitstragegriff und 6 mm blendfreies Schutzglas



## SPECIFICATIONS

<b>Aspect Ratio</b>	0.672916667
<b>Panel Type</b>	98" IPS/ D-LED, 86"IPS / E-LED
<b>Effective display area (W x H) (mm)</b>	1895.0 x 1065.9 mm
<b>Auflösung</b>	3840 x 2160
<b>Brightness (typ.)</b>	500 cd/m2
<b>Response Time</b>	8 ms (G to G)
<b>Viewing angle [(T/B)/(L/R)]</b>	178°/178° (CR≥10)
<b>Terminals   HDMI In</b>	HDMI TYPE-A Connector x 2
<b>Terminals   DVI-D IN/AUDIO IN (L/R)</b>	DVI-D 24-pin x 1/ Stereo Mini Jack (M3) x 2 (Shared with PC In)
<b>Terminals   PC IN/AUDIO IN (L/R)</b>	Mini D-sub 15-pin x 1/ Stereo Mini Jack (M3) x 2 (Shared with DVI-D In)
<b>Terminals   DisplayPort IN</b>	DisplayPort x 1
<b>Terminals   DisplayPort OUT</b>	DisplayPort x 1
<b>Terminals   USB</b>	USB Connector (TYPE A) x 2, DC 5 V/2 A (USB 3.0 supported)
<b>Terminals   Serial</b>	D-sub 9-pin x 1, RS232C Compatible
<b>Terminal   LAN</b>	RJ45 x 1, 10 BASE-T / 100 BASE-TX, Compatible with PLink™
<b>Terminal   DIGITAL LINK</b>	RJ45 x 1, 100 BASE-TX, Compatible with long reach mode and PLink™
<b>Terminals   Slot</b>	Intel® SDM specification Corresponding size SDM-S / SDM-L, Supply power 12 V / 5.5 A, 3.3 V / 1.1 A
<b>Terminals   IR IN / OUT</b>	Stereo Mini Jack (M3) x 1 / x 1
<b>Terminals   Audio Out</b>	30 W [15 W + 15 W] 10% THD
<b>Built-in Speaker</b>	20 W [10 W + 10 W]
<b>Power Requirements</b>	110-127 V AC, 50/60 Hz, 220-240 V AC, 50/60 Hz
<b>Wall-hanging pitch (mm)</b>	600 x 400 mm VESA Compliant
<b>Wall-hanging pitch (inch)</b>	23.6" x 15.8" VESA Compliant
<b>Operating Time</b>	24 h/day
<b>Operating Environment</b>	Temperature : 0 °C to 40 °C / Humidity: 20% to 80% (Non-condensation)
<b>Orientation</b>	Landscape/Portrait (Angle adjustment is not possible for portrait installation.)
<b>Tilting angle</b>	0-20 degrees forward/backward with landscape/portrait setting
<b>Operating Environment   Humidity</b>	0 °C to 40 °C (32°F to 104°F) Altitude 0~1400 m (4593 ft)/0 °C to 35 °C (32 °F to 95 °F) Altitude 1400 ~2800 m (4593 ft to 7874 ft)
<b>Operating environment   Temperature</b>	20% to 80% (Non-condensation)
<b>Screen Size</b>	98" and 86"

URL: <https://business.panasonic.de/visuelle-systeme/sq1-ir-serie>

## CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>