



FPS-1031 Version: 3

Parallel Print Server

Product Overview

The LevelOne FPS-1031 print server is an ideal network printing solution for small offices, home offices, schools and other businesses that require printer sharing over the same network. This print server is equipped with a 10/100Mbps autosensing Ethernet port and a DB-36-pin male bi-directional Centronic port that connects to parallel printers.

Multi OS and Network Printing Protocol Support

The FPS-1031 is a print server with 1 parallel port that supports Windows ME, 2000, XP and Vista operating systems as well as Mac OS 8.1 and higher, UNIX/Linux and Netware (Bindery/NDS).

Network Protocol supported includes TCP/IP, IPX, NetBEUI, AppleTalk, LPR and SMB over TCP/IP for flexible use with different network clients connected to the same office network. The FPS-1031 also includes Internet Printing Protocol (IPP) support and Windows Print Monitor Technology to monitor printing jobs received.

Easy Installation Wizard

The LevelOne FPS-1031 is easily configurable using a Web Browser or the Windows based configuration program included with the CD-ROM. The print server is easily managed through a Web based user interface and the firmware is upgradeable through TFTP, the Windows set-up program or the Web based user interface.

Key-features

- Parallel Printer Server für gemeinsame Druckernutzung im Netzwerk
- Einfaches Einrichten über benutzerfreundliche Oberfläche
- Unterstützt verschiedene Netzwerk-Druckprotokolle
- Unterstützt verschiedene Betriebssysteme

Specifications

Systemeigenschaften

Standards & Protokolle:

IEEE 802.3, 802.3u Ethernet Standards

Speicher:

2Mbytes SDRAM

Buchse:

1x 10/100Mbps Auto-sensing RJ-45 port



Taster:
1xButton(Reset/Load Default/Self-test print)

Indikator:
Power
LAN

Leistungsaufnahme:
5VDC/1A Switching

Energieverbrauch:
1.3 Walt

Datenrate:
740 KB/sec

Funktionen

Allgemein:
LPR,RAW TCP,IPP,SMB,
AppleTalk
Netware Bindery/NDS
Print Monitor
Bonjour printing

Management:
Web
PSAdmin
Telnet

Environment

Temperatur bei Betrieb (°C):
Operating?0 ~ 50?; Storage?-5 ~ 65 ?

Luftfeuchtigkeit bei Betrieb:
Operating?0 ~ 70%; Storage?0 ~ 80%

Abmessungen


Abmessungen (W x D x H mm):
56 (Length) x 57 (Width) x 22 (Height) mm

Gewicht:
50.6g (Device Only)

Approval and Compliance

Zertifizierung:
CE, FCC

Diagramm



Order Information

FPS-1031

Package Contents

FPS-1031

Netzadapter

Quick Installation Guide

Ressource CD (Bedienungsanleitung, Hilfsprogramm, Treiber)

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.