

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6

Page 2 of 14

Under normal conditions of use, the battery is hermetically sealed, NOT considered hazardous. Stated from the official reply of U.S. Department of Labor, Lithium -ion batteries have the potential to leak, spill, or break, cannot be considered an article that requires Safety Data Sheet. The SDS meets the requirement of the United States Occupational Safety and Health Administration (OSHA) 2012 Hazard Communication Standard 29 CFR 1910.1200.

Section I – Product and Company Identification

Information of Product

Product Identity (As Used on Label and List)	Lithium Ion cell/battery
---	--------------------------

Information of Manufacturer

Manufacturer's Name

GPI International Ltd.

Emergency Telephone Number

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-527-3887

Address (Number, Street, City State, and ZIP Code)

7/F, Building 16W,
16 Science Park West Avenue
Hong Kong Science Park,
New Territories, Hong Kong

Telephone Number for Information

852-2484-3333

Date of prepared and revision


12th Jan, 2018 RC6

Recommended use of the chemicals:

Don't directly connect (+) and (-) of a battery to make a short circuit. Don't disassemble, heat or put the battery into fire.

Section II – Hazards Identification

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6

Page 3 of 14

Classification:

i) **Under normal conditions of use**, the battery is hermetically sealed, NOT considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). It does not pose a physical hazard or health risk.

ii) **In considering the potential to leak, spill, or break**, if the electrolyte inside is leaked, hazardous material may be released and classified as following hazards.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2



GHS Label elements, including precautionary statements:

i) **Under normal conditions of use**, the battery is hermetically sealed, no hazards are available.


GHS Label: Not applicable with normal use.

IATA Label:

Accept combination use of either previous and new labels.

	
<i>Class 9 DG Label</i> <i>Used until 31 December 2018.</i>	<i>Lithium Ion Battery Handling Label</i> <i>Used until 31 December 2018.</i>
	
<i>Class 9 Lithium Batteries DG Label</i>	<i>Lithium Battery Mark</i>

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6

Page 4 of 14

- ii) In considering the potential to leak, spill, or break, if the electrolyte inside is leaked, hazardous material may be released and the following is for emergency overview.

Labels



Signal word

Danger

Hazard Statements

Harmful if swallowed

Cause skin irritation

May cause an allergic skin reaction


Causes serious eye irritation

May cause cancer

May cause damage to organs through prolonged or repeated exposure

May explode if heated

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6

Page 5 of 14

Precautionary Statements

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Do not breathe dust/fume/gas/mist/vapours/spray

Avoid breathing breathe dust/fume/gas/mist/vapours/spray

Wash hands thoroughly after handling

Do not eat, drink or smoke when using this product

Response Refer to Section IV – First-aid Measures

Storage Refer to Section VII – Handling and Storage


Disposal The battery cell remains in the environment. Do not throw it out into the environment.
Disposal of contents/container in accordance with local regulation.

Specific Hazards Not available

Section III – Composition/Information on Ingredients

Material/Ingredients	CAS #	Approximate % of total weight
Aluminum	7429-90-5	3-6%
Carbon	7440-44-0	15-30%
Copper	7440-50-8	7-13%
Lithium Cobaltate (LiCoO ₂)	12190-79-3	0-45%
Lithium Manganate (LiMn ₂ O ₄)	12057-17-9	0-20%
Lithium Iron Phosphate	15365-14-7	0-55%
Polyvinylidene fluoride (PVDF)	24937-79-9	0.1-5%
Carboxymethyl cellulose (CMC)	9004-32-4	0.1-5%
Nickel	7440-02-0	0.1-10%
Ethyl methyl carbonate	96-49-1	1-10%
Dimethyl carbonate	616-38-6	1-15%
Ethylene carbonate	623-53-0	1-10%
1,3-propanesulfone	1120-71-4	0-1%

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6

Page 6 of 14

Section IV – First-aid Measures

Inhalation	If electrolyte vapors are inhaled, remove from exposure and provide fresh air, seek medical attention if respiratory irritation develops. Ventilate the contaminated area.
Skin Contact	If electrolyte leakage occurs and makes contact with skin, wash with plenty of water immediately. Remove contaminated clothing and wash before reuse. In severe cases obtain medical attention.
Eye Contact	If electrolyte comes into contact with eyes, wash with copious amounts of water for fifteen (15) minutes, and contact a physician.
Ingestion	Wash out mouth thoroughly with water and give plenty of water to drink. Obtain medical attention.


Section V – Fire-fighting Measures

Extinguishing Media	Carbon Dioxide, Dry Chemical or Foam extinguishers can be used for battery BUT water extinguisher is not suitable.
Unusual Fire and Explosion Hazards	In case of fire, it is permissible to use Carbon Dioxide, Dry Chemical or Foam extinguishers on these cells or their packing material. Cool exterior of cells if exposed to fire to prevent rupture.
Special Protective equipment and Precautions for fire-fighters	Fire fighters should wear self-contained breathing apparatus.

Section VI – Accidental Release Measures

Personal Precautions, protective equipment, emergency procedures	Cells that are leakage should be handled with rubber gloves. Avoid direct contact with electrolyte. Wear protective clothing. Remove personnel from area until fumes dissipate. If the skin has come into
---	---

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6

Page 7 of 14

	contact with the electrolyte, it should be washed thoroughly with water.
Containment and Clean Up	Sand or earth should be used to absorb any exuded material. Seal leaking battery and contaminated absorbent material in plastic bag and dispose of as Special Waste in accordance with local regulations.

Section VII – Handling and Storage


Precautions for Safe Handling	Do not expose the battery to excessive physical shock or vibration. Short-circuiting should be avoided, however, accidental short-circuiting for a few seconds will not seriously affect the battery. Prolonged short circuits will cause the battery to rapidly lose energy, could generate enough heat to burn skin, and may cause the safety release vents of the enclosed cells to open. Sources of short circuits include jumbled batteries in bulk containers, coins, metal jewelry, metal covered tables, or metal belts used for assembly of batteries in devices. To minimize risk of short-circuiting, the protective case supplied with the battery should be used to cover the terminals when transporting or storing the battery. Do not disassemble or deform the battery. Should an individual cell within a battery become ruptured, do not allow contact with water.
Conditions for Safe Storage	Keep cells between -20°C and 35°C for prolong storage. When the cells are closed to fully charged, the storage temperature should be between -20°C and 30°C and should be controlled at 10-20°C during transportation and packed with efficient air ventilation. Do not store in disorderly fashion, or allow metal objects to be mixed with stored cells.

Section VIII – Exposure Controls/Personal Protection

Exposure Control Limit - Only for reference when electrolyte is leaked.

Common Chemical Name / General Name	OSHA PEL	ACGIH TLV
Aluminum metal (as Al)	TWA 15 mg/m ³ (total) TWA 5 mg/m ³ (resp)	-

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6

Page 8 of 14

Cobalt metal (As Co)	TWA 0.1 mg/m ³	TWA 0.02 mg/m ³
Carbon (Artificial graphite)	15mg/m ³ (total) 5mg/ m ³ (respirable)	-
Manganese compounds (as Mn)	(Ceiling) 5 mg/m ³	TWA 0.02 mg/m ³ (resp.)
Nickel, metal and insoluble compounds	(as Ni) TWA 1 mg/m ³	Elemental: 1.5mg/m ³ (IHL); Insoluble inorganic compounds: 0.2mg/m ³ (IHL)
Copper	0.2mg/m ³ (fume) 1.0mg/m ³ (a coarse particulate, mist)	-
Organic electrolyte	-	-

TWA – Time Weighted Average

ACGIH TLV: American Conference of Governmental Industrial Hygienists Threshold Limit Value

OSHA PEL: Occupational Safety & Health Administration Permissible Exposure Limit

Personal protective equipment

Required when electrolyte is leaked.

Respiratory protection: Protective mask

Hand protection: Protective gloves

Eye protection: Protective glasses designed to protect against liquid splashes

Skin and body protection: Working clothes with long sleeve and long trousers

Engineering Control

No engineering measure is necessary during normal use. In case of internal leakage of cell materials, operate the local exhaust or enhance ventilation

The contents of cell are hermetically sealed.

Section IX – Physical and Chemical Properties

Appearance


Cylindrical or prismatic shape

Odor

Odorless

Odor Threshold

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6


Page 9 of 14

	N.A.
pH	Melting point/freezing point
N.A.	N.A.
Initial boiling point and boiling range	Flash point
N.A.	N.A.
Evaporation rate	Flammability (solid, gas)
N.A.	N.A.
	Upper/lower flammability or explosive limits
	N.A.
Vapor pressure	Vapor density
N.A.	N.A.
Relative density	Solubility
N.A.	N.A.
Partition coefficient: n-octanol/water	Auto-ignition temperature
N.A.	N.A.
Decomposition temperature	Viscosity
N.A.	N.A.

Section X – Stability and Reactivity

Reactivity	N.A.
Chemical stability	Stable under normal use
Possibility of hazardous reactions	By misuse of a battery cell or the like, gas accumulates in the cell and the internal pressure rises. These gases may be emitted through the gas release vent. When fire is near, these gases may take fire. When a battery cell is heated strongly by the surrounding fire, acrid or harmful fume may be emitted.
Conditions to avoid	Direct sunlight, high temperature and high humidity

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6

Page 10 of 14

Materials to avoid	Conductive materials, water, seawater, strong oxidizers and strong acids
Hazardous decomposition products	Acid or harmful fume is emitted during fire.

Section XI – Toxicological Information

Route of Entry

Inhalation	N.A.
Skin	N.A.
Ingestion	Ingestion of a battery can be harmful.

Health Hazard (Acute and Chronic) / Toxicological Information

There is no toxicity data for Battery. The battery is nontoxic because the chemical mixture from battery is sealed by the metal container.

In case of electrolyte leakage, skin will be itchy when contaminated with electrolyte.

In contact with electrolyte can cause severe irritation and chemical burns.

Inhalation of electrolyte vapors may cause irritation of the upper respiratory tract and lungs.

Section XII – Ecological Information

Persistence/degradability :

Since a battery cell and the internal materials remain in the environment, do not bury or throw out into the environment.

Section XIII – Disposal Considerations

Recommended methods for safe and environmentally preferred disposal :


Product (waste from residues)

Do not throw out a used battery cell. Recycle it through the recycling company.

Contaminated packaging

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates them, dispose them as industrial wastes subject to special control.

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158


Revision: C6

Page 11 of 14

Section XIV – Transport Information

UN Number: UN3480						
UN Proper Shipping Name: Lithium ion batteries						
UN: The Transport of Dangerous Goods, Manual of Tests and Criteria 38.3 Lithium batteries						
Shipping mode	Regulation	Packing Group/Special Provision	Limit of Wh	Transport Hazard Class	Environmental Hazards	Special Precautions
USA	US DOT 49 CFR Section 173-185 Lithium batteries and cells		>20Wh(cell) >100Wh(battery)	Dangerous goods, Class 9	No marine pollutant	Lithium handling label needed
			<=20Wh(cell) <=100Wh(battery)	Non-dangerous goods	No marine pollutant	Lithium handling label needed
Air	ICAO/IATA DGR 59 th edition	- PI965 Section IA	>20Wh (cell) >100Wh (battery)	Dangerous goods, Class 9	No marine pollutant	DG Label, CAO Label needed
		- PI 965 Section IB	<=2.7, 2.7 to 20Wh (Cell); <=2.7, 2.7 to 100Wh (battery) (for that exceed allowance in Section II)			Lithium handling label, DG label, CAO label needed
		- PI 965 Section II	<=2.7, 2.7 to 20Wh (Cell); <=2.7, 2.7 to 100Wh (battery) (Only allow one package prepared per consignment)	Partially-regulated dangerous goods	No marine pollutant	Lithium handling label, CAO Label needed.
Sea	IMO/IMDG CODE 38-16	P903 SP188	>20Wh(cell) >100Wh(battery)	Dangerous goods, Class 9	No marine pollutant	Lithium handling label needed
			<=20Wh(cell) <=100Wh(battery)	Non-dangerous goods	No marine pollutant	Lithium handling label needed
Road/Rail	ADR/RID	P903 P903a P903b	>20Wh(cell) >100Wh(battery)	Dangerous goods, Class 9	No marine pollutant	Lithium handling label needed
			<=20Wh(cell) <=100Wh(battery)	Non-dangerous goods	No marine pollutant	Lithium handling label needed

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158

Revision: C6

Page 12 of 14

a) In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for GP Lithium ion batteries (sometimes referred to as "Lithium ion battery") has been designed to be compliant with these regulatory concerns.

Rechargeable lithium ion batteries (UN 3480), are forbidden for transportation aboard passenger-carrying aircraft. Such batteries transported in accordance with Section IA, IB & II of Packing Instruction 965 must be labeled with the CARGO AIRCRAFT ONLY label. Lithium ion cells and batteries must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated design capacity.

b) International Maritime Organization (IMO) IMDG Code regulated these products as UN 3480, Lithium ion batteries, Class 9 dangerous goods with Special Provision 188 and Packing Instruction 903 assigned.

The watt-hour of the models can be referred to the appendix (Model list – WI-RD-P03-164).

Transport of Lithium ion batteries contained in equipment or Lithium ion batteries packed with equipment have to follow the appropriate regulations for UN3481. PI967, PI966 should be followed accordingly for Air Transport.


Section XV – Regulatory Information

Special requirement be according to the local regulations.

Section XVI – Other Information

The data in this Safety Data Sheet relates only to the specific material designated herein. However, the data is provided without any warranty; expressed or implied, regarding its correctness or accuracy. It is the user's responsibility to assume liability on loss, injury, damage, or expense resulting from improper use of this product. Any previous MSDS of this product mentioned above are hereby replaced with this new document. We urge you to make this information available as appropriate in your organization and to any others with whom you arrange to handle this product.

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries

Document Number: WI-RD-P03-158


Revision: C6

Page 13 of 14

文件履歷表

版次	制定/修訂內容	制定/修訂頁次	制定/修訂日期
A0	初版發行	N	2013.01.13
A1	加鋰電型號	P6	2013.01.21
A2	精縮電池型號	P6-P8	2013.04.01
A3	Add the IIb model list	P8	2013.04.19
A4	1、 Add the page of history 2、 增加電池型號 XP1015-10S 3、 IATA DGR 54th edition to IATA DGR 55th edition. 4、 IMDG Code 35-10 to IMDG Code 36-12	P6	2013.12.23
A5	精縮電池型號	P7	2014.01.13
A6	Date of prepared and revision 改為 14 th Feb,2014	P2	2014.02.14
A7	Date of prepared and revision 改為 20 th March,2014	P2	2014.03.20
A8	1、增加電池型號 ICR18650-26F 2、 Add the IIA model list	P8 P6	2014.05.30
A9	1、增加電池型號 XP0620-05S/GP0620-05S XP0620-05SN/GP0620-05SN PP0620-05S/PP0620-05SN 2、 Date of prepared and revision 改為 27 th Jun,2014	P7 P2	2014.06.27
B0	1、 增加電池型號 GP1012-08S 2、 Section XV 增加 Transportation Information	P7 P5	2014.10.10
B1	1、 0620 電池 Rated voltage 改為 3.8、 Watt hour 改為 0.209 2、 修改 GP1012-08S 電池 Rated capacity (Ah) 為 0.08 3、 刪減電池型號	P7-P10	2014.12.04
B2	增加電池型號： GP1048-49S， 修改模板內容	All	2015.01.01
B3	New format	All	2015.1.9
B4	Add model 18650-29HD	P9	2015.1.22
B5	New SDS format	All	2015.02.03
B6	Amend the composition	P2, P3	2015.02.09
B7	Amend models	P10	2015.03.30
B8	Amend Models	P10	2015.05.30
B9	Delete model list	P10	2015.07.30
C0	Amend version of Section XIV	P8	2016.01.05
C1	Amend address of company	P2	2016.02.16

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Safety Data Sheet for GP Lithium ion rechargeable cells/batteries


Document Number: WI-RD-P03-158

Revision: C6

Page 14 of 14

C2	Amend section III	P2	2016.03.15
C3	Corrected Lithium Iron Phosphate CAS# from 15365-14-17 to 15365-14-7	P3	2016.04.01
C4	Amend Section I, XI, XIV, XVI	P.2, 10-12	2016.12.20
C5	Amend Section I, II, III, XIV	P.2-5, 12	2017.12.20
C6	Amend section XIV PI #	P.12	2018.1.12

Remark: "N.A. is indicated if not applicable



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.