



Dell Multifunction Printer - E515dn



Versatility meets value for easy office efficiency.

Boost office productivity with an easy-to-use 4-in-1 multifunction printer with essential productivity features for everyday printing tasks.

- Easily print, scan, fax and copy with features such as the automatic document feeder (ADF) and built-in duplexer for automatic two-sided printing.
- Get connected easily using the Dell Printer Easy Installer.
- Simplify printing tasks and maintenance with the Dell Printer Hub¹.

Simple set-up

Get your Dell printer up and running easily using the Dell Printer Easy Installer and allow flexible connectivity with Ethernet and USB connectivity options.

Designed for convenience

Scan or copy up to 35 sheets hands-free with the ADF and reduce paper use up to 50% using automatic two-sided printing.

Help simplify record keeping by copying both sides of an ID card on a single side of paper using the "ID Copy" button.

Print more with less interruptions using the optional high yield toner cartridge that prints up to 2,600 pages² for greater savings. Minimize maintenance with the single fuser unit designed to last the life of the printer, and a cassette input paper tray that keeps paper dust-free.

Printing on-the-go

Print directly from compatible smartphones, tablets, and other mobile devices with the Dell Document Hub app, available on the App Store, Google Play and the Windows Store. The E515dn also supports AirPrint³, Google Cloud Print and Mopria, so you can print from nearly any mobile device connected to the same network as your E515dn.⁴



One-stop solution to do more

Simplify your printing tasks and printer maintenance using Dell Printer Hub¹. This convenient, one-stop solution with an intuitive interface that integrates printer essentials and cloud connectivity for easy document management and control of your printer.

- 1-click to update printer firmware and software
- 1-click to execute customized scan shortcuts
- 1-click access to the Dell Document Hub cloud access solution, which also features cloud Optical Character Recognition to convert scans into editable, searchable files.

Receive automatic alerts when firmware and software updates are available, or when the toner runs low. Conveniently re-order toner via Dell Printer Hub.

Eco-conscious design

The E515dn meets the latest regulatory and environmental standards, including ENERGY STAR[®] qualification⁵ and Restriction of Hazardous Substances (RoHS) compliance⁶. It also supports printing on recycled, renewable content and chlorine-free paper.

Comprehensive services

Connect to technical support for any printing issues via phone or online during your standard 1-year Limited Hardware Warranty⁷, and enjoy 1-year Advanced Exchange⁶ after Remote Diagnosis Service⁸.

Stay covered longer when you choose optional 2-, 3-, 4-, or 5-year extended Limited Hardware Warranty⁹. Get dedicated support 24/7 with Dell ProSupport^{™10} service options.

[Learn more at Dell.com/printers](https://www.dell.com/printers)

Dell Multifunction Printer - E515dn

Printer specifications	Printer type	Mono multifunction printer (Print, Copy, Scan, Fax)
	Print speed¹¹	
	Simplex (600 x 600 dpi)	Up to 27 ppm (letter) and 26 ppm (A4)
	Duplex (600 x 600 dpi)	Up to 15 ppm (letter) and 13 ppm (A4)
	First page out time (simplex letter, 600 dpi)	From Ready state - as fast as 8.5 seconds From Power Saver mode - as fast as 17.5 seconds
	Print resolution	600 x 600 dpi (Up to 2400 x 600 dpi)
	Operation panel	2-line LCD screen
	Print language	
	Printer driver language	PCL 6, PostScript™ Level 3 Emulation, XPS
	Printer data stream	PCL 6, PostScript™ Level 3 Emulation
	Fonts	HP PCL® 6 Emulation: 66 scalable fonts, 12 bitmap fonts PostScript 3: 66 scalable fonts
	Processor speed	266 MHz
	Memory, standard	64 MB RAM
	Mobile printing support	Dell Document Hub (or Android, iOS and Windows 8 and later), AirPrint ³ , Google Cloud Print, Mopria-certified
Usage rate	Duty cycle	Up to 10,000 pages per month ¹²
	Recommended monthly print volume	300 - 1,000 pages per month
Scan specifications	Scan type	Flatbed, ADF / Contact Image Sensor (CIS)
	Scan speed (Single-page document, 300 x 300 dpi)	Up to 17 ipm mono / up to 6 ipm color
	Scan resolution	600 x 1200 dpi, up to 19200 x 19200 dpi (software enhanced)
	Scan depth	Color: 24-bit; Mono: 8 bit for gray scale
	Scan size (max)	Flatbed: 210 mm (8.3") x 291 mm (11.5") / ADF: 210 mm (8.3") x 350 mm (13.8")
	Scan to media (file format)	JPEG, TIFF, BMP, PDF, XPS
	Walk-up scan to	FTP (Network server), PC
Copy specifications	Copy speed (Single-page document, 600 x 600 dpi)	Up to 20 copies per minute (cpm) (letter) / up to 19 cpm (A4)
	Maximum copies	99
	Enlarge	25 to 400%
	Copy settings	Stack/Sort, N in 1 (2-in-1, 4-in-1), ID Copy (2-in-1), Autofit
Fax specifications	Fax transmission speed	Up to 33.6 Kbps
	Speed dial	Up to 200 entries
	Memory size	8 MB
	Fax feature	Broadcast, Delay/Schedule, Priority, Secure, Forward
Paper handling	Input sources	Standard: 250-sheet input tray, single-sheet feeder / Maximum: 251 sheets
	Automated Document Feeder (ADF) Specifications	
	Capacity	35 sheets
	Media size	A4 Short Edge Feed (SEF), Letter SEF
	Types	Plain, Recycled
	Output destinations	Standard: 100-sheet bin; Maximum: 100 sheets
	Standard tray	
	Types and weights supported	Plain Paper (16 - 28 lb/60 - 80 g/m ²), Recycled paper
	Sizes	A4, A5, A5L, A6, US Letter, B5 (JIS), Executive, US Legal, Folio
	Single-sheet feeder	
	Types and weights supported	Plain Paper (16 - 28 lb/60 - 80 g/m ²), Recycled paper, Thick Paper (28 - 43 lb/ 80 - 105 g/m ²), Bond, Label, Envelope
	Sizes	A4, A5, A5L, A6, US Letter, B5 (JIS), Executive, US Legal, Folio, Com10, Monarch, C5, DL
	Duplexer	
	Types supported	16~58 lb (60 to 105 g/m ²), Plain, Thin, Thick, Bond, Recycled, Label, Envelope
	Sizes	A4, US Letter, B5 (JIS), A5, A5L, A6, Executive, US Legal, Folio
	Page layout options	Portrait or Landscape orientation, Multiple copies, Multi-page printing (N-up), Duplex printing (only for Windows and Mac Driver), Poster (only for Windows Driver), Watermarks (only for Windows Driver), Collate
	Printable area	8.17" x 13.7" (207.4 mm x 347.1 mm)

Connectivity	Interfaces	USB 2.0 High Speed, Ethernet 10/100BASE-TX
Operating systems		Microsoft® Windows® Server 2003 / Windows® Server 2003 x64 Edition
	Windows	Windows® Vista Windows® Server 2008 / Windows® Server 2008 R2 Windows® 7 Windows® 8/8.1 Windows® Server 2012 / Windows® Server 2012 R2
	Macintosh	Apple Mac OS® X 10.7x, 10.8.x, 10.9.x, 10.10x
	Others	RedHat Enterprise Linux Desktop 6 (x32/x64) SUSE Linux Enterprise Desktop 11 (x32/x64) Ubuntu 12.04 LTS (x32/x64)
Physical specifications	Printer dimensions (W x D x H)	16.1" x 15.7" 12.5" (409 mm x 398.5 mm x 316.5 mm)
	Printer weight	25.4 lbs (11.5 kg) (with consumables)
	Shipping dimensions (W x D x H)	24.5" x 20.4" x 19.7" (623 mm x 517 mm x 499 mm)
	Shipping weight	34.4 lbs (15.6 kg)
	Operating environment	Temperature: 50°F to 90°F (10°C to 32.5°C); Relative Humidity: 20% to 85% RH, non-condensing; Altitude: <6,560 ft (<2,000 m)
	Storage (packaged)	Temperature: 32°F to 95°F (0°C to 35°C); Relative Humidity: 10% to 80% RH; Altitude: <6,560 ft (<2,000 m)
	Acoustics (Pressure/Power)¹⁵	Printing (simplex): 50.0 dB / 6.5 B; Standby: 33 dB / 4.6 B
Power specifications	Voltage	120 vac model: 110 to 120 vac 50 Hz / 60 Hz nominal
	Power consumption	Printing mode: 480W (120 vac model) Standby mode: < 60W (120 vac model) Power Saver mode (Sleep): ≤ 5.8 W/h (120 vac)
Consumables	Ship-with toner capacity²	Up to 700 capacity (Black)
	Standard toner capacity²	Up to 1,200 page capacity (Black)
	High-yield toner capacity²	Up to 2,600 page capacity (Black)
	Imaging drum	Up to 12,000 pages
Product certifications	Safety and EMC: EN 60950-1/IEC 60950-1, EN 55022 (Class B); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; CE Mark (EU); UL 60950-1 / CAN/CSA-C22.2 No. 60950-1-07; ICES-003 (Canada; US CFR Title 47, FCC Part 2 and 15B, Part 15C and Part 68; FDA/DHHS (21CFR, Chapter 1, Subchapter J; RCM (Australia); Telepermit (New Zealand); SABS/ICASA (South Africa); NOM NYCE (Mexico); GS Mark (Germany) Others: ROHS Compliant; WEEE; REACH; ENERGY STAR qualified; ErP Lot 4; ErP Lot 6 and 26; Blue Angel Certified	
Supported languages	English, French, German, Italian, Spanish, Danish, Norwegian, Dutch, Swedish	
Printer management	Dell Printer Hub, Dell Open Print Driver (OPD), Dell OpenManage Printer Manager v2 (OMPM), Standard Printer MIB	
Contents in box	Dell Multifunction Printer - E515dn, Software and Documentation CD, Ship-With Black Cartridge (700 page yield ²), Power Cord, USB Cable, RJ11 Cable, Setup Guide	



Dell E310/514/515 series Black Toner Cartridge, 1,200 page yield²



Dell E310/514/515 series High Yield Black Toner Cartridge, 2,600 page yield²



Imaging drum, up to 12,000 pages

1. Supports Windows 7, 8 and later only.
2. Toner yield based on testing in accordance with ISO/IEC 19752. Yields vary with usage and environmental conditions.
3. AirPrint-enabled printers work with iPad, iPhone (3GS or later), and iPod touch (3rd generation or later) running iOS 4.2 or later.
4. The printer and the mobile device must be connected on the same network.
5. For details on energy efficiency of ENERGY STAR® qualified products, refer to: www.energystar.gov.
6. Meets the requirements of the EU RoHS Directive 2011/65/EU on the Restriction of the use of certain Hazardous Substances (RoHS).
7. For copy of Ltd Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see www.dell.com/warranty.
8. Replacement system or replacement part will be dispatched, if necessary, following phone-based troubleshooting, in advance of receipt of returned defective part or system. Replacements may be refurbished. Defective unit must be returned. Availability varies. Other conditions apply.
9. Remote Diagnosis is determination by online/phone technician of cause of issue; may involve customer access to inside of unit and multiple or extended sessions. If issue is covered by Limited Hardware Warranty and not resolved remotely, technician and/or part will be dispatched, usually within 1 business day following completion of Remote Diagnosis. Availability varies. Other conditions apply.
10. Availability and terms of Dell Services vary by region. For more information, visit Dell.com/servicecontracts/global.
11. Actual print speed may vary with use. Measured in accordance with ISO/IEC 24734 methodology.
12. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.
13. Tested in accordance with ISO 7779 and reported in accordance with ISO 9296. Acoustics - Declared noise emission values of computer and business equipment.

©2015 Dell Corporation Limited. Dell, the Dell logo and Dell Toner Management System are registered trademarks or trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Microsoft, Windows and Windows NT are registered trademarks or trademarks of Microsoft Corporation. Android and Google Cloud Print are registered trademarks of Google Inc. iPad, iPhone, iPod, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. AirPrint and the AirPrint logo are trademarks of Apple Inc. Specifications are subject to change without notice.

Dell cannot be responsible for errors and omissions in typography or photography.

