

# UTA-06

GaN III Universal Travel Adapter with  
2x USB-C PD 100W & QC 4+ / 2x USB-A QC 3.0



GaN III charging technology



Charge 5 devices at once



Compact design



World-to-World adapter

## Charge around the world

The Verbatim GaN III Universal Travel Adapter UTA-06 is a compact and versatile solution for travelers. It supports over 180 countries, offering EU, UK, US, Australia, and China plug options. Utilizing advanced GaN III technology, it's more efficient and compact.

This 5-in-1 adapter allows simultaneous charging of five devices through AC and USB ports, including two USB-C with Power Delivery 3.0 (with PPS support), Quick Charge 4+ output, up to 100W each, and two USB-A ports support Quick Charge 3.0 output, up to 18W each.

Ideal for international travel, this adapter ensures you are never without power on the go.

# UTA-06

GaN III Universal Travel Adapter with  
2x USB-C PD 100W & QC 4+ / 2x USB-A QC 3.0

PN	Description	Bar Code	EAN128 Code	EAN14 Code
32121	Verbatim UTA-06 GaN III Universal Travel Adapter with 2 x USB-C PD 100W & QC 4+ / 2 x USB-A QC 3.0	023942321217	(02)00023942321217(37)20(91)489	50023942321212

## General Information

Input Plug Formats	Type A / B / C / E / F / G / I / J / L / N
Output Plug Formats	EU, UK, USA/Japan, AUS/China Type A / B / C / D / E / F / G / H / I / J / K / L / M / N / O
Material	Fire-proof polycarbonate, Copper (Pouch: Nylon + PVC)
Product Dimensions LxWxH (mm)	92 x 55 x 54
Product Weight (grams) approx	264
Colour	Black
Safety shutter	Yes, can only be opened with force of more than 75N (7.5Kg) per hole

## Power

AC Input	100-250V, 50-60Hz
Rating	100-250V, 10A Max, 2500W Max
Total DC Output	100.0W
Earthed Plug	No
Fuse	10A, 250V (spare fuse included)
Fuse Compliance	BS1362
Charging Technology	PD3.0, QC4+, FCP, SCP, AFC, PPS, BC1-2 and more

## Single Port Output

USB-C1 PD 3.0 & QC 4+ (PPS supported)	3.3-11V=5 A, 5.0V=3.0A, 9.0V=3.0A, 15.0V=3.0A, 20.0V=5.0A 100.0W Max.
USB-C2 PD 3.0 & QC 4+ (PPS supported)	3.3-11V=5 A, 5.0V=3.0A, 9.0V=3.0A, 15.0V=3.0A, 20.0V=5.0A 100.0W Max.
USB-A1 QC 3.0	5.0V=3.0A, 9.0V=2.0A, 12.0V=1.5A 18.0W Max.
USB-A2 QC 3.0	5.0V=3.0A, 9.0V=2.0A, 12.0V=1.5A 18.0W Max.

Multiport Max Output	USB-C1	USB-C2	USB-A1	USB-A2
USB-C1+USB-C2	65W	35W	-	-
USB-C1+USB-A1	65W	-	18W	-
USB-C1+USB-A2	65W	-	-	18W
USB-C2+USB-A1	-	20W	18W	-
USB-C2+USB-A2	-	20W	-	18W
USB-C1+USB-C2+USB-A1	65W	20W	18W	-
USB-C1+USB-C2+USB-A2	65W	20W	-	18W
USB-C1+USB-A1+USB-A2	65W	-	15W	15W
USB-C2+USB-A1+USB-A2	-	20W	15W	15W
USB-C1+USB-C2+USB-A1+USB-A2	65W	20W	15W	15W

# UTA-06

GaN III Universal Travel Adapter with  
2x USB-C PD 100W & QC 4+ / 2x USB-A QC 3.0

**Verbatim**<sup>™</sup>  
Technology you can trust

Other Features	
Indoor use	Yes
Outdoor use	No
LED Indicators	Yes
Protective Functions	Safety shutter for child protection; can only be opened with force of more than 75N (7.5Kg) per hole
Compliance	EN 55032:2005/A11:2020 EN 55035:2017/A11:2020 EN IEC61000-3-2: 2019/A1:2021 EN 61000-3-3: 2013/A1:2019 EN IEC 62638-1:2020+A11:2020
ROHS Directive	2011/65/EC
Electromagnetic Compatibility	2014/30/EC
General product Safety	2001/95/EC

Storage and Operating Conditions	
Storage Temperature	-20°C to 85°C
Operating Temperature	0°C to 35°C
Operating Humidity	25% to 90% RH

Logistic Information	
Pack Dimensions LxWxH	90.6 x 62.7 x 120.6 mm (147.6 mm with hanger)
Pack Weight	375 g
Pcs per Pack	1
Outer Cartons Dimensions	330 x 250 x 200 mm
Outer Cartons Weight	8 000 g
Pcs per Outer Carton	20
Outer Carton per Layer	12
Layers per Pallet	6
Pcs per Pallet	1 440



# UTA-06

GaN III Universal Travel Adapter with  
2x USB-C PD 100W & QC 4+ / 2x USB-A QC 3.0

**Verbatim**  
Technology you can trust



Front



Back



Right angled UK plug



Right angled EU plug



Left angled USB



Right angled USB



Packaging flat



Packaging 3D

## Pack Contents:

- GaN III Universal Travel Adapter
- Travel pouch
- Quick Start Guide

## Warranty

- 2 Year Limited Warranty

## Warning

- THIS IS NOT A VOLTAGE CONVERTER
- FOR INDOOR USE ONLY
- NO GROUNDING: THIS PRODUCT IS FOR USE WITH UNEARTHED OR DOUBLE INSULATED APPLIANCES ONLY

For more information, please  
contact your key account manager

Publication date: 03-11-2023  
© 2023 Verbatim. All rights reserved.  
All brand names are registered trademarks of their respective owners.  
Unauthorized use strictly prohibited.  
Specifications are subject to change without prior notice.