



<b>Model</b>	<b>Optix MAG301CR2DE</b>
Introduction	<p>Werte dein Gaming-Rig mit dem passenden Gaming-Bildschirm auf! Der MSI Optix MAG301CR2DE ist die erste Wahl für anspruchsvolle Gamer: Der hochauflösende WFHD-Bildschirm liefert mit 200 Hz und der AMD FreeSync Premium-Technologie schlierenfreie und gestochen scharfe Bilder. Der erweiterte Farbraum mit 103% sRGB-Abdeckung sorgt für realistische und lebendige Darstellung. Die starke R1500-Krümmung des Curved-Displays ist fürs PC-Gaming ausgelegt – und lässt dich direkt ins Spiel eintauchen.</p> <p>Höhenverstellbar und kipp- sowie schwenkbar findet der Monitor schnell und genau die gewünschte Position. Das Gaming-OSD bietet praktische Gaming-Features und lässt sich per App auch vom Windows-Desktop aus steuern.</p> <p>Trotz großer 29,5“-Diagonale sieht der Optix MAG301CR2DE mit seinem schlanken rahmenlosen Design und der Mystic Light Rückbeleuchtung zudem noch unwiderstehlich gut aus.</p>
Selling Points	<ul style="list-style-type: none"> <li>• Große 29,5“-Diagonale und hohe 2560x1080 WFHD-Auflösung</li> <li>• R1500 Curved Design – perfekt fürs Gaming</li> <li>• 200-Hz-Refreshrate für blitzschnellen Bildaufbau</li> <li>• 1 ms Reaktionszeit sichert schlierenfreie Bilder</li> <li>• FreeSync Premium für maximale Bildwiederholrate und flüssige Bilddarstellung</li> <li>• 103% Abdeckung des sRGB-Farbraums</li> <li>• 178° Wide View Technik – starke Darstellung aus allen Blickwinkeln</li> <li>• Höhenverstellbar und kippbar für exakte Ausrichtung</li> <li>• Gaming-OSD steuerbar mit Joystick oder Windows-App</li> <li>• Einstellbare Mystic Light RGB-Rückbeleuchtung für coolen Gaming-Look</li> <li>• Augenschonend mit Anti-Flicker- und Less-Blue-Light-Technik</li> <li>• Schlankes, rahmenloses Design</li> <li>• Die ideale Ergänzung zu MSI Gaming-PCs und Komponenten</li> </ul>
Bilder und Logos	<a href="#">Produktanlage Optix MAG301CR2DE</a>

<b>Model</b>	
SKU Number	9S6-3CB45H-011
Brand	MSI
Series Name	Gaming
MKT Name	Optix MAG301CR2DE
Color	ID1/Black-Black
<b>Display</b>	
Screen Size	29.5" (75 cm)
Active Display Area (mm)	690.432(H)*291.276(V)mm
Curvature	Curve 1500R
Panel Type	VA
Resolution	2560x1080 (WFHD)
Pixel pitch	0.2697(H)X0.2697(V)
Aspect Ratio	21:9
Dynamic Refresh Rate technology	FreeSync Premium
HDR (High dynamic range)	HDR ready
Brightness (nits)	300

Contrast Ratio	3000:1
DCR (Dynamic Contrast Ratio)	100000:1
Signal Frequency	66~245 KHz(H) / 30~200 Hz(V)
Refresh Rate	200HZ
Response Time (MPRT)	1ms(MPRT)
Response Time (GTG)	4ms
Response Time (Tr + Tf)	20ms
View Angles	178°(H)/178°(V)
NTSC (CIE1976 area percentage/overlap)	90%(Typ)/85%(TYP)
NTSC (CIE1931 area percentage/overlap)	82%(Typ)/80%(TYP)
sRGB (CIE1976 area percentage/overlap)	103%(Typ)/90%(TYP)
sRGB (CIE1931 area percentage/overlap)	103%(Typ)/95%(TYP)
Adobe RGB (CIE1976 area percentage/overlap)	88%(Typ)/83%(TYP)
Adobe RGB (CIE1931 area percentage/overlap)	84%(Typ)/80%(TYP)
DCI-P3 (CIE1976 area percentage/overlap)	82%(Typ)/81%(TYP)
DCI-P3 (CIE1931 area percentage/overlap)	85%(Typ)/84%(TYP)
Rec.709 (CIE1976 area percentage/overlap)	104%(Typ)/90%(TYP)
Rec.709 (CIE1931 area percentage/overlap)	115%(Typ)/95%(TYP)
Surface Treatment	Anti-glare
Touch Screen	Non-touch
Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)
Note_DP	2560 x1080 (Up to 200Hz)
Note HDMI	2560 x1080 (Up to 200Hz)
Note DVI	N/A
<b>I/O Ports</b>	
HDMI	2
HDMI version	2.0
HDMI HDCP version	NA
DisplayPort	1
DisplayPort version	1.2
DisplayPort HDCP version	NA
Thunderbolt	NA
Thunderbolt version	NA
Thunderbolt HDCP version	NA
USB Type C (DisplayPort Alternate)	NA
DVI	NA
D-Sub	NA
Mic-in	NA
Headphone-out	1
Audio Combo	NA
USB 2.0 Type A	NA
USB 2.0 Type B	NA
USB 2.0 Type C	NA
USB 3.2 Gen 1 Type A	2
USB 3.2 Gen 1 Type B	1
USB 3.2 Gen 1 Type C	NA
USB 3.2 Gen 2x2 Type C	NA
USB 3.2 Gen 2x2 Type A	NA
Card reader	N/A
Lock type	Kensington Lock
<b>Power</b>	
Country	DE
Territory	EU
Entity	DE
Power Type	External Adaptor 19V 4.74A
Power Input	100~240V, 50/60Hz

<b>Warranty</b>	
Warranty	3 Jahre Pick Up & Return
<b>Design</b>	
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Height)	0 ~ 110 mm
Adjustment (Pivot)	-90° ~ 90°
VESA Mounting	75x75mm
Frameless Design	Yes
<b>Pallet</b>	
pallet Q'ty (by air) pcs	10
Q'ty/20cy (by air) pcs	100
Q'ty/40cy (by air) pcs	210
Dimension (L)(by air) mm	N/A
Dimension (W)(by air) mm	N/A
Dimension (H)(by air) mm	N/A
Net Weight (by air) kg	N/A
Gross Weight (by air) kg	N/A
pallet Q'ty (by sea) pcs	20
Q'ty/20cy (by sea) pcs	200
Q'ty/40cy (by sea) pcs	420
Dimension (L)(by sea) mm	N/A
Dimension (W)(by sea) mm	N/A
Dimension (H)(by sea) mm	N/A
Net Weight (by sea) kg	N/A
Gross Weight (by sea) kg	N/A
<b>Inside Carton Dimension (WxDxH)</b>	
Inside Carton Dimension (WxDxH) (mm)	785 x 197 x 452
Inside Carton Dimension (WxDxH) (inch)	30.91 x 7.76 x 17.8
<b>Outer Carton Dimension (WxDxH)</b>	
Outer Carton Dimension (WxDxH) (mm)	803 x 210 x 475
Outer Carton Dimension (WxDxH) (inch)	31.61 x 8.27 x 18.7
<b>Product Dimension with Stand (WxDxH)</b>	
Product Dimension with Stand (WxDxH) (mm)	703 x 287 x 512
Product Dimension with Stand (WxDxH) (inch)	27.68 x 11.3 x 20.16
<b>Product Dimension without Stand (WxDxH)</b>	
Product Dimension without Stand (WxDxH) (mm)	703 x 103 x 320
Product Dimension without Stand (WxDxH) (inch)	27.68 x 4.06 x 12.6
<b>Stand Dimension (WxDxH)</b>	
Stand Dimension (WxDxH) (mm)	N/A
Stand Dimension (WxDxH) (inch)	N/A
<b>Weight</b>	
Weight (Net kg)	5.8
Weight (Net lbs)	12.79
Weight (Gross kg)	8.21
Weight (Gross lbs)	18.1
<b>Accessories</b>	
DisplayPort Cable	1
HDMI Cable	1
DVI Cable	0
USB Type A to Type B Cable	1
USB Type C to Type A Cable	0
USB Type C to Type C Cable	0
Thunderbolt Cable	0
VGA Cable	0
3.5mm audio Cable	0
3.5mm combo audio Cable	0

Power Cord	1
AC Adaptor	1
Quick Guide	1
Warranty Card	1
<b>Barcode Info</b>	
EAN	4719072748746
UCC14	10824142223571
UPC	824142223574
JAN	