

# GEP-2021 20-Port Gigabit PoE Switch, 16 PoE Outputs, 2 x Gigabit RJ45, 2 x Gigabit SFP, 802.3at/af PoE, 270W

## **Product Images**











# **Short Description**

- 16 Gigabit PoE ports, 2 Gigabit ports and 2 Gigabit SFP slots.
- Total PoE power budget: 270W, up to 30W per port.
- IEEE 802.3af/at PoE compliant to simplify deployment and installation.
- Supports DIP switch configuration for VLAN mode and Default mode features.
- Supports port-based VLAN.
- 6KV surge protection, 6KV/8KV ESD protection.

## **Description**

The GEP-2021 is LevelOne latest generation of 20-Port Gigabit Unmanaged PoE Switch, with 2 Gigabit RJ45 and 2 Gigabit SFP Uplink ports. also offers powerful DIP switch button configuration for VLAN mode and Default mode features. Switch that gives you a high-performance, low-cost, easy-to-use, seamless upgrade to boost your network to 1000Mbps. Increase the speed of your network backbone to a massive 40Gbps and bring Gigabit speeds all the way to your computers.

The GEP-2021 PoE-enabled switches features an IEEE 802.3af/at certified, better PoE functionality with 270W PoE power budget and usability. supports up to 16 ports at 15.4W, or 9 ports at 30 W to meet the increasing

power demands of users, giving you flexibility in power allocation for a variety of powered devices enabling you to scale your operations to meet business growth, operational cost savings, and ease of management.

#### **Additional Information**

Approval and compliance CE, RoHS Max. operating humidity (%) 90 Max. operating temperature (°C) 50 Max. storage temperature (°C) 85 Min. operating temperature (°C) -10

Min. storage temperature (°C) -40 Backplane (Gbps) 40Gbps Packet buffer 29.8Mpps

VLAN mode, Default mode Dip switch

Power, Link/Act, PoE usage rate(20%, 40%, 60%, 80%, Indicators

90%)

MAC address table 8K Flash memory size 4M

Mount 19" rack mount, Desk mount

Pin assignment and polarity 1/2 (+), 3/6 (-)

Power supply AC100-240V, 50/60Hz

Chipset RTL8332L

• IEEE 802.3 10-BASE-T (Ethernet) • IEEE 802.3u 100-BASE-Standards

TX (Fast Ethernet) • IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) • IEEE 802.3z 1000BASE-X (Gigabit Ethernet) •

IEEE 802.3 af/at

• Heat dissipation: 86,435 BTU/hr • MTBF: 250,000 hr **Features** 

 $(25^{\circ}C)$ 

Product weight (kg) 4 Product breadth (mm) 442 285 Product depth (mm) 44 Product height (mm) Color Black

**FAN** 4015867223895

Model number GEP-2021

• GEP-2021 • Power Cord • 19" Rack Mount Kit • Quick Package contents

Installation Guide

Gigabit RJ45 2 Uplink ports (10/100/1000Base-T) Gigabit SFP 2 Uplink ports (1000Base-X SFP slots) 802.3af/at PoE 16 Downlink ports (10/100/1000Base-T)

Grade Commercial Data Rate **Gigabit Ethernet** 

**PoE Supported** Yes Manageable No **Fanless** Nο

Total20.00 Concurrent ports Total270.00 PoE Power Budget

