

ViewSonic® PROJECTOR

PX701-4K

Key Features

- True 4K HDR visual experience
- World's lowest 5ms input lag & 240Hz high refresh rate
- Warping, auto V keystone and H/V keystone for flexible installation
- 3,200 ANSI Lumens offering bright images in any environment
- Larger screen size with lower cost-per-inch



Product Description

The PX701-4K is a 3,200 ANSI Lumens high brightness 4K home projector, a great-value choice for upgrading to 4K. Take in impressive visuals in true 4K clarity supporting HDR/HLG, or upgrade your gaming experience to the next level with the world's lowest 5ms input lag and 240Hz refresh rate. Powerful warping, auto V keystone, H/V keystone and 4-corner adjustment make setting up an up-to-300" big screen on any surface easier than ever. Adding on to that is the energy-efficient 20,000 hours long lamp life, making it even more favourable to lowering total cost of ownership.



1. Power Key
2. Keypad
3. Front IR
4. Zoom/Focus Ring
5. HDMI X 2
6. AC In
7. RS-232

8. Audio Out
9. Kensington Lock
10. USB Type A(5V/1.5A)

Visit Us  www.viewsonic.com

SPECIFICATION

| | |
|---|-----------------------------------|
| Native Resolution: | 3840x2160 |
| DMD Type: | DC3 |
| Brightness: | 3200 (ANSI Lumens) |
| Contrast Ratio with SuperEco Mode: | 12000:1 |
| Display Color: | 1.07 Billion Colors |
| Light Source Type: | Lamp |
| Light Source Life (hours) with Normal Mode: | 6000 |
| Light Source Life (hours) with SuperEco Mode: | 20000 |
| Lamp Watt: | 203W |
| Lens: | F=2.0-2.05, f=15.843-17.445mm |
| Projection Offset: | 120%+/-6% |
| Throw Ratio: | 1.5-1.65 |
| Optical Zoom: | 1.1x |
| Digital Zoom: | 0.8x-2.0x |
| Image Size: | 30 |
| Throw Distance: | 1m-10.96m, (100 |
| Keystone: | H:+/-40° , V:+/-40° |
| Audible Noise (Normal): | 31dB |
| Audible Noise (Eco): | 27dB |
| Input Lag: | 5ms |
| Resolution Support: | VGA(640 x 480) to 4K(3840 x 2160) |
| HDTV Compatibility: | 720p, 1080i, 1080p, 2160P |
| Horizontal Frequency: | 15K-129KHz |
| Vertical Scan Rate: | 23-240Hz |

INPUT

| | |
|-------|-------------------------------|
| HDMI: | 2 , (HDMI 2.0b/ HDCP 1.4/2.2) |
|-------|-------------------------------|

OUTPUT

| | |
|---------------------|--------------|
| Audio out (3.5mm): | 1 |
| Speaker: | 10W |
| USB Type A (Power): | 1 (5V/ 1.5A) |

CONTROL

| | |
|------------------------|---|
| RS232 (DB 9-pin male): | 1 |
|------------------------|---|

OTHERS

| | |
|--|-----------------------------------|
| Power Supply Voltage: | 100-240V+/- 10%, 50/60Hz, (AC in) |
| Power Consumption: | Normal: 290W, Standby: <0.5W |
| Operating Temperature: | 0~40°C |
| Net Weight: | 2.8kg |
| Dimensions (WxDxH) with Adjustment Foot: | 312x222x108mm |

| | |
|---------------|---|
| OSD Language: | English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages |
|---------------|---|

STANDARD ACCESSORY

| | |
|-----------------|-----|
| Power Cord: | 1 |
| Remote Control: | 1 |
| QSG: | Yes |

OPTIONAL ACCESSORY

| | |
|--------------------|-------------|
| Lamp/Light Source: | RLC-126 |
| Carry Bag: | PJ-CASE-008 |