imagePROGRAF TX-3100 MFP Z36

A 36-INCH MULTIFUNCTION PRINTER WITH ADVANCED PRINT AND SCAN TECHNOLOGY FOR ACCELERATED PRODUCTIVITY

High-productive, multifunction large format inkjet printer for CAD production and poster, with improved usability and flexibility.





Faster printing

Increased print speed and continuous printing enhances productivity, up to 3.2ppm A1 CAD

• Quality in print and scan

Class-leading inkjet and unique scanner technology assure high-quality printing and scanning

Accurate media handling

Added support for high-volume printing, with hassle-free media handling, automatic media switching for dual roll option

Security assured

Improved security features supporting the industry requirement

Improved usability

Redesigned UI and control panel ensure intuitive user experience in operation

• Effortless creation

Updated software solutions assist efficient poster design and high-volume printing of drawings

Weather resistance

Full pigment LUCIA TD ink provides greater durability with the water resistant media option



PRODUCT RANGE



imagePROGRAF TX-4100 MFP Z36



imagePROGRAF TX-3100



imagePROGRAF TX-4100



TECHNICAL SPECIFICATIONS

SingleSensor

36" (914mm)

6" (150mm)

38" (965mm)

0.07 - 1.0mm

None / Canon black

SmartWorks MFP V6

Calibration target
Assembly & Start Up Guide
USB3 cable (2 meter)

736 scanner

(not included).

2,400 x 1,200 dpi

5 pl per colour

13ips

3ips

6ips

1056 x 199 x 118mm

8m (JPEG/PDF), 15,2m (TIFF)

Europe: CE mark Other Countries : CB certfication

3.0 (backward compatible to USB2) Stop, Advance, Rewind, LED status

250 Scanner
Suspension mount for printer and system controller mount
2 paper edge guides
3 Document return guides

Windows 10 Enterprise LTSC 64 bit. CPU: Intel Pentium G5400T. SSD: 256GB, RAM: 8GB DDR4. Display: Multi touch 15.6", 1366 x 768. 3 x USB3 & 1 x USB2, 1 x GbE (rear). Power button and 1 x USB3 (Front).

Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head $x\ 1$ print head)

Total : 15,360 nozzles $\,$ MBK : 5,120 nozzles $\,$ BK, C, M, Y : 2,560 nozzles each

1,200 dpi x 2 includes Non-firing nozzle detection and compensation system $\,$

Bundled Starter Ink: 330ml (MBK)/160ml (BK, C, M, Y) Sales Ink: 160ml/330ml/700ml

Microsoft Windows 32 Bit: 7, 8.1, 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows Server 2008R2, 2012, 2012R2, 2016, 2019 Apple Macintosh: macOS 10.12.6-macOS 10.15

HP-GL/2, HP RTL, PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)

Pigment inks: 5 colour MBK/BK/C/M/Y

128GB (Physical memory 2GB) Expansion slot : No

500GB (Encrypted)

Power Supply 15.6" system controller 3:1 Trident power cord - requires 1 local mains cable

Rear (front eject via Document Return Guide)

1200dpi

Flat

78Ka

imagePROGRAF TX-3100 MFP Z36

SCANNER TECHNOLOGY

Scan technology Optical Resolution (dpi)

Paper path Scan width

Min. scan width Document width

Max. scan length Weight of scanner

Dimensions W x D x L

Compliances Front/rear exit

Document handling - Face up/

Document thickness (1)

Scan speed 8-bit grayscale & mono @200dpi (2)

Scan to PC: Scan speed 24-bit color @200dpi (2)

Copy: Scan speed 24-bit color @200dpi (2)

Interface USB

Scanner controls Branding/Colour Software Included

What's in the box?

System controller

PRINTER TECHNOLOGY

Printer Type Print Technology

Print Resolution **Number of Nozzles**

Line Accuracy Nozzle Pitch

Ink Droplet Size

Ink Capacity

Ink Type OS Compatability

Printer Languages Standard Interfaces

Standard memory Hard Drive

PRINTING SPEED CAD Drawing Plain Paper (A1)

Poster:

Plain Paper (A0)

Heavy coated Paper (A0)









MEDIA HANDLING

Media Width

Minimum Printable Length

Media Core Size

Media Feed Capacity

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) and Weight (Kg)

WHAT'S INCLUDED What's in the Box?

Software Included

OPTIONS Optional Items

USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b CONSUMABLES User Replaceable Items

Thicker documents must be flexible and the paper return guides removed and may require additional support. Some media should be scanned at reduced speeds. It is not possible to guarantee to be able to scan all media types and sizes.

The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times and quoted top speeds will depend on the host performance and are not guaranteed for all media types. Scan times quoted are the maximum for true 200 x 200ctpl image capture. Max scan speed for RGB: Copying at 200/300/600dpi = 6/4/2ips. Scanning at 200/300/600dpi = 37/8.6/4.3ips. Scanning at 200/300/600dpi = 13/8.6/4.3ips.

Notes & Recommendations

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and *: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Canon Inc. canon.com

Canon Europe canon-europe.com

English edition

© Canon Europa N.V.,2021

Media Feed and Output

Media Thickness

Maximum Printable Length

Maximum Media Roll

Margins Recommended area

Margins Printable area

Media Take-up roll unit

Borderless Printing Width (Roll Only)

Maximum number of delivered prints [Multi-position basket]

used with hole of platen

Standard position: 1 sheet Flat position: 42 landscape, glossy paper 10 sheets, Coated paper 20 sheets, Plain paper 20 sheets Basket position: 1 sheet (excludes curled condition)
Folding position: A0/A1 portrait, CAD drawing, Plain
paper 20 sheets, Uncoated paper 100 sheets (excludes curled condition)
Stacking position: AI/AZ landscape, CAD drawing, Plain
paper 100 sheets, Uncoated paper 100 sheets
(excludes curled condition)

Roll Paper : One Roll, Front-loading, Front Output (Manual feed using media locking lever)

Roll paper: 18 m (Varies according to the OS and

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Roll paper : Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless) : Top: 0 mm, Bottom: 0 mm,

Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 12.7 mm, Side: 3 mm

Roll Paper: Two rolls. Automatic switching is possible. Cut Sheet: 1 sheet

Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

[Recommended] 515mm(JIS B2), 594mm(ISO A1), 728mm(JIS B1), 841mm(ISO A0), 10", 14", 17", 24", 36" [Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 6", 8", 12", 15", 16", 18", 20", 22", 30", 34", 300mm, 500mm, 600mm, 800mm and custom roll width (152.4 - 917mm) ""Printable" size is printed as micro marzin tecnology, that means is not

Roll paper : 152.4mm - 917mm Cut sheet 152.4mm - 917mm

Internal diameter of roll core: 2"/3"

Roll/Cut : 0.07mm = 0.8mm

Roll paper: 101.6mm Cut sheet: 203.2 mm

application) Cut sheet : 1.6 m

170 mm

imagePROGRAF TX-3100 MFP Z36 1469 x 984 x 1473 mm (Basket Open, Scanner Upper Position) 1469 x 766 x 1422 mm (Basket Closed, Scanner Lower Position) 129 kg (including Roll Holder Set and Roll unit, Scanner, Suspension mount, System controller, excluding ink and print heads)

Printer, 1 x Print Head, 1 x Roll holder (spool), 3" Paper Core Attachment, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard, Environment Leaflet User software CD-ROM (Windows), PosterArtist Lite CD-ROM EU Biocide Sheet, Eurasian Economic Union Sheet,

Important Information Sheet

imagePROGRAF TX Printer Driver and PosterArtist Lite Other software available as Download from Web.

2/3" Roll Holder: RH2-34 Roll Unit : RU-32 Stacker : SS-31

Ink Tank: PFI-110 (160ml), PFI-310 (330ml), PFI-710 (700ml) Print Head: PF-06 Cutter Blade: CT-07 Maintenance Cartridge: MC-30

DISCLAIMER







0:42 (Fast) 1:15 (Standard)

1:38 (Fast) 2:33 (Standard)



