

# ThinkVision P34w-20

## DISPLAY

### Panel Size

34.14-inch

### Screen Dimensions

812.1 mm x 359.5 mm

### Panel Type

In-Plane Switching

### Active Area

799.8 mm x 334.8 mm

### Curvature

3800R

### Backlight

WLED

### Aspect Ratio

21:9

### Resolution

3440 x 1440

### Pixel Pitch

0.2325 mm x 0.2325 mm

### Dot/Pixel Per Inch (DPI/PPI)

109

### Viewing Angle (H x V @ CR 10:1)

178° / 178°

### Response Time

4ms (Extreme Mode)

6ms (Normal Mode)

### Refresh Rate

60 Hz

### Brightness (Typical)

300 cd/m<sup>2</sup>

### Contrast Ratio (Typical)

1000:1

### Dynamic Contrast Ratio (Typical)

3M:1

### Color Gamut

99% sRGB

### Color Support (Typical)

1.07 Billion

### Color Depth

8-bit + FRC

### HDR Compliance

Yes

### Anti-glare

Yes

## CONNECTIVITY

### Video Signal

1 x USB3.2 Gen1 Type-C (DP 1.2 Alt Mode)

2 x HDMI 2.0

1 x DP 1.2

1 x DP Out

### Audio Signal

1 x Audio Out (3.5 mm)

### USB Hub

Yes

### Ethernet

Yes (10M/100M/1000M)

### USB Upstream

1 x USB3.2 Gen1 Type-C

1 x USB3.2 Gen1 Type-B

### USB Downstream

1 x USB3.2 Gen1 Type-C

3 x USB3.2 Gen1 Type-A

### DaisyChain Support

Yes (DP Out)

## MULTI-MEDIA

### Integrated Speakers

Yes (2 x 3W)

## SPECIAL FEATURES

### Factory Calibration

Yes (Avg. Delta E<2)

### PIP/PBP

Yes

### KVM Switch

Yes

### Software

Lenovo ThinkColour (Lenovo Display

Control Center)<sup>2</sup>

## POWER

### Power Consumption (Typ. / Max)

36W / 230W

### Power Consumption Sleep/ Off Mode

<0.5W

### Power Consumption Sleep/Off Mode

<0.3W

### ENERGY STAR Power Consumption (Pon/E<sub>TEC</sub>)

30W / 93kWh

### Power Supply

Internal

### USB Type-C Power Delivery (W)

Up to 100W

### Smart Power

Yes

### Voltage Required

AC 100 to 240 V (50-60 Hz)

## MECHANICAL

### Tilt Angle (Front/Back)

-5° / 35°

### Swivel Angle (Left/Right)

-45° / 45°

### Lift (Max. Range)

150 mm

### VESA Mount Capability

Yes (100 x 100 mm)

### ThinkCentre M Series Tiny Support

Yes, by Tiny Monitor Clamp II

(PN: 4XH0Z42451<sup>7</sup>)

### ThinkCentre M Series Nano Support

Yes, by Nano Monitor

Clamp II (PN: 4XH0Z42451<sup>7</sup>)

### Kensington Lock Slot

Yes

### Cable Management

Yes

### Bezel Color

Raven Black

### Bezel Width (Side)

9.5 mm

### Bezel Width (Top/Bottom)

9.5 / 28.4 mm

## DIMENSION

### Size Packed (D x H x W) (mm/inch)

220.0 x 475.0 x 937.0 mm

8.66 x 18.70 x 36.89 inches

### Size Unpacked w/ Stand (D x H x W)

(mm/inch) (Lowest Position)

245.0 x 469.3 x 817.3 mm

9.65 x 18.48 x 32.18 inches

### Size Unpacked w/ Stand (D x H x W)

(mm/inch) (Highest Position)

245.0 x 621.4 x 817.3 mm

9.65 x 24.46 x 32.18 inches

### Size Unpacked w/o Stand (Head Only)

(D x H x W) (mm/inch)

76.8 x 372.7 x 817.3 mm

3.02 x 14.67 x 32.18 inches

### Weight Packed (kg/lbs.)

15.5 kg / 34.2 lbs.

### Weight Unpacked (kg/lbs.)

10.8 kg / 23.8 lbs.

### Weight (Monitor Head Only) (kg/lbs.)

7.4 kg / 16.2 lbs.

## WHAT'S IN THE BOX

Monitor with stand

1 x Power cable (1.8m)

1 x DP cable (1.8m) (NA only)

1 x USB Type-C to Type-A cable

(1.8m) (NA only)

1 x USB Type-C cable (1.8m)

Factory calibration report

Quick setup guide

## CERTIFICATION

### ENERGY STAR Certification

Yes

### CCC

Yes

### TCO

9.0

### EPEAT

Gold

### RoHS (EU/2011/65)

Yes

### Windows Certification

Windows 10, Windows 11

### China Energy Efficiency Standard

Tier 1

### TÜV Rheinland Eye Comfort

Yes

### TÜV Rheinland Low Blue Light

Yes

### TÜV Rheinland Flicker Free

Yes

### TÜV Low Blue Light (Hardware Solution)

Yes

### Eyesafe Display Certification

Yes



<sup>1</sup> USB Type-C and USB-C are registered trademarks of USB Implementers Forum. | <sup>2</sup> This software can only be used with Windows 10 & Windows 11. | <sup>3</sup> Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration and may decline with downstream USB ports connected or higher brightness setting. | <sup>4</sup> True Split is available with USB-C or DisplayPort connection in Windows only; not supporting in MAC OS. | <sup>5</sup> HDR10 only. | <sup>6</sup> For selected Lenovo notebooks. | <sup>7</sup> Sold separately.

Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: 5 Gbit/s for USB 3.2 Gen 1; 10 Gbit/s for USB 3.2 Gen 2 & 20 Gbit/s for USB 3.2 Gen2x2.

© 2022 Lenovo. All rights reserved. These products are available while supplies last. Prices shown are subject to change without notice. For any questions concerning price, please contact your Lenovo Account Executive. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC 27709, Attn: Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkVantage, and ThinkVision are trademarks or registered trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside, Intel Core, and Core Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks or service marks of others.

Specifications may vary depending upon region.