

RGB-LED-Projektoren erzeugen lebendige Bilder mit sehr guter Farbwiedergabe

PT-LRZ35

Perfekt für die Zusammenarbeit, Besprechungsräume und gemeinschaftliche Arbeitsumgebungen



KEY FEATURES

- 1 Chip DLP, 3.500 lm, WUXGA, RGB-LED
- RGB-LED-Lichtquelle nutzt gesonderte LEDs für perfekte Bildqualität
- Bis zu 20.000 Stunden wartungsfrei
- Kontrast 30.000:1 (Full On/Full Off)
- Optionale Software: Multi Monitoring & Control Software, Early-Warning-Software



SPECIFICATIONS

Projector type	1-Chip DLP™ projector
DLP™ chip Panel size (mm)	17.0 mm (0.67 in) diagonal, 16:10 aspect ratio
DLP™ chip Panel size (inch)	0.67 in diagonal, 16:10 aspect ratio
DLP™ Chip Display Method	DLP™ chip x 1, DLP™ projection system
DLP™ chip Number of Pixels	2,304,000 (1920 x 1200 pixels)
Light Source	Light Emitting Diode

Light output*1	3,500 lm
Time until light output declines to 50 %*2	20,000 hours
Auflösung	1920 x 1200 pixels
Contrast Ratio*1	30,000:1 (When [Light Power] is set to [Normal] and [Picture Mode] is set to [Dynamic])
Screen size [diagonal] (mm)	1.02–7.62 m (40–300 in), 16:10 aspect ratio
Screen size [diagonal] (inch)	40–300 in, 16:10 aspect ratio
Center-to-corner zone ratio*1	90 %
Lens	1.3x manual zoom (throw ratio: 1.28–1.69:1)
Lens shift Vertical (from center of screen)	Vertical: +50 %, +40 %
Keystone Correction Range	Vertical: ±30 %
Installation	Ceiling/floor, front/rear, 2-axis 360-degree installation
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-T, compatible with PJ Link™ (Class 1)
Power Supply	AC 100-240 V, 50/60 Hz
Power Consumption	NORMAL: 420 W, ECO: 255 W, QUIET: 196 W
Operation noise*1	NORMAL: 35 dB, ECO: 27 dB, QUIET: 24 dB
Dimensions (W x H x D) (mm)	375 x 124*3 x 314 mm (14 3/4" x 4 7/8" *3 x 12 3/8") (including protruding parts)
Dimensions (W x H x D) (inch)	375 x 124*3 x 314 mm (14 3/4" x 4 7/8" *3 x 12 3/8") (including protruding parts)
Weight*4	Approx. 6.7 kg (14.8 lbs)
Operating Environment	Operating temperature: 0–40 °C (32–104 °F)*5, operating humidity: 20–80 % (no condensation)
Applicable Software	Multi Monitoring & Control Software, Early Warning Software
Note	*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *2 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcastcontents, under conditions with 30 °C (86 °F), 1,400 m above sea level, and 0.15mg/m3 of particulate matter. Estimated time until light output declines to 50 % varies depending on environment. *3 With legs at shortest position. *4 Average value. May differ depending on the actual unit.*5 Note that the projector cannot be used at altitudes exceeding 4,200 m (13,780 ft) above sea level. 4,200 m (13,780 ft) above sea level is the maximum elevation at which performance can be guaranteed. In the following operating environments, light output may be reduced to protectthe projector: when the projector is used at altitudes below 1,400 m (4,593 ft) and ambient temperature exceeds 40 °C (104 °F); when the projector is used at altitudes between 1,400 m (4,593 ft) and 2,700 m (8,858 ft) exclusive and ambient temperature exceeds 35 °C (95 °F); andwhen the projector is used at altitudes between 2,700 m (8,858 ft) and 4,200 m (13,780 ft) exclusive and ambient temperature exceeds 30 °C (86 °F).
Built-in Speaker	10 W monaural
Terminals Audio In 1	M3 stereo mini-jack x 1
Terminals Variable Audio Out	M3 stereo mini-jack x 1
Terminals Audio In 2	M3 stereo mini-jack x 1
Terminals Computer 1 In	D-sub 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Terminals HDMI In 1/HDMI In 2	HDMI 19-pin x 2 (HDCP and Deep Color compatible), CEC supported
Terminals Video In	Pin jack x 1
Terminals DC Out	USB Connector (Type A) x 1 (for power supply, DC 5 V/2 A)
Terminals Computer 2 In	D-sub 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Terminals Computer Out	D-sub 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Terminals Micro USB	1 (for service use)

URL: <https://business.panasonic.de/visuelle-systeme/pt-lrz35>

CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>