

FEU-0812 8-Port Fast Ethernet Switch

Product Images



Short Description

- Provides flexibility of 8 x 10/100BASE-TX ports
- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- Quick and easy installation
- Supports 1K MAC address auto-learning and auto-aging
- Simple Plug and Play installation

Description

The LevelOne FEU-0812 is a wire-speed, non-blocking networking device that provides 8 ports 10/100 Mbps Ethernet connections. All ports support auto-negotiation and auto-MDI/MDIX sensing, eliminating the need for crossover cables or Uplink Ports. Each port can be used as general network port or as connecting port into a router, server, hub or another network switch.

Approval and compliance	● CE ● RoHS
Max. operating humidity (%)	90
Max. operating temperature (°C)	45
Max. storage humidity (%)	90
Max. storage temperature (°C)	70
Min. operating humidity (%)	10
Min. storage humidity (%)	5
Min. storage temperature (°C)	-40
Backplane (Gbps)	1.6 Gbps
Packet buffer	1.19 Mpps
Indicators	● Power ● Link/Active
MAC address table	1 K
Mount	Desk mount, Wall mount
Power supply	Input : 5VDC, 0.55A (External Power Adapter)
Chipset	IP178G
Standards	● IEEE802.3 (10BASE-T) ● IEEE802.3u (100BASE-T) ● IEEE802.3az (Energy Efficient Ethernet) ● IEEE802.3x
Product weight (kg)	0.11
Product breadth (mm)	130.7
Product depth (mm)	52.3
Product height (mm)	20
Color	Black
EAN	4015867226667
Model number	FEU-0812
Package contents	● FEU-0812 ● Power Adapter ● Quick Installation Guide ● Declaration of Conformity
Grade	Commercial
Data Rate	Fast Ethernet
PoE Supported	No
Manageable	No
Fanless	Yes
Concurrent ports	Total8.00
Power consumption	1.7 W

