https://www.viewsonic.com/global/products/sheet/VG2756-2K

ViewSonic Medical VG2756-2K

Key Features

- Integrated USB TypeC and Ethernet
- Daisy chain monitor
- Ergonomic design
- vDisplay Manager software for multitasking
- Lower total cost of ownership



Product **Description**

The ViewSonic VG56 docking monitor series will keep the workstation tidy and productive with USB Type-C and Ethernet connectivity that turn your monitor into a hub for charging, data, network, and devices. With a 27" display and 2560 X 1440 resolution that delivers larger and clearer images, the VG2756 QHD monitor expands your productivity. This monitor's DisplayPort output also makes it convenient to daisy chain monitors, reducing clutter on your desk and simplifying cable management. A range of ergonomic features such as 40-degree tilt, swivel, bi-directional pivot and height adjustment, along with eye-care technology let you stay comfortable at work all day. In addition, the supported vDisplay Manager software for multi-tasking provides efficient on-screen display control. The monitor and quick release stand ship in an eco-friendly, biodegradable package, thus minimizing total cost of ownership.

Visit Us – www.viewsonic.com

×
Wir kennen Ihre Datenschutzpräferenzen noch nicht.
Datenschutz einstellen

https://www.viewsonic.com/global/products/sheet/VG2756-2K

10.22, 09:22		nttps://www.view	sonic.com/global/products/sl	neet/VG2/56-2K
	Display Size (in):	27	INPUT SIGNAL Frequency Horizontal:	15 ~ 90KHz
	Display Size (in.): Viewable Area (in.):	27	Frequency Vertical:	49 ~ 75Hz
	Panel Type:	IPS Technology	VIDEO INPUT	49~7502
	Resolution:	2560 x 1440		TMDS - HDMI (v1.4), PCI-E -
	Resolution Type:	QHD (Quad HD)	Digital Sync:	DisplayPort (v1.2), Micro-Packet - Type C
	Static Contrast Ratio:	1,000:1 (typ)	ERGONOMICS	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	Dynamic Contrast Ratio:	80M:1	Height Adjust (mm):	130
	Light Source:	LED	Swivel:	120°
	Brightness:	350 cd/m² (typ)	Tilt (Forward/Back):	-5° / 40°
	Colors:	16.7M	Pivot (Right/Left):	90° / 90°
	Color Space Support:	8 bit true	WEIGHT (IMPERIAL)	
	Aspect Ratio:	16:9	Net (lbs):	15.2
	Response Time (Typical GTG):	5ms	Net Without Stand (Ibs):	9.9
	Response Time (GTG w/OD):	5.8ms	Gross (lbs):	22.5
	Viewing Angles:	178º horizontal, 178º vertical	WEIGHT (METRIC)	
			Net (kg):	6.9
	Backlight Life (Hours):	30000 Hrs (Min)	Net Without Stand (kg):	4.5
	Curvature:	Flat 60	Gross (kg):	10.2
	Refresh Rate (Hz): Blue Light Filter:	60 Yes	DIMENSIONS (IMPERIAL) (W	/XHXD)
			Packaging (in.):	27.2 x 16.9 x 8.6
	Flicker-Free:	Yes	Physical (in.):	24.1 x 15.99~20.99 x 8
	Color Gamut:	NTSC: 78% size (Typ) sRGB: 110% size / 100% coverage	Physical Without Stand (in.):	24.1 x 14.2 x 2
		(Тур)	DIMENSIONS (METRIC) (WX	HXD)
	Pixel Size:	0.233 mm (H) x 0.233 mm (V)	Packaging (mm):	692 x 430 x 218
	Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical (mm):	612 x 406.19~533.24 x 202
	COMPATIBILITY	0500 4440	Physical Without Stand (mm):	612 x 362 x 52
	PC Resolution (max):	2560x1440	GENERAL	
	Mac® Resolution (max):	2560x1440	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO, UKCA, RCM
	PC Operating System:	Windows 11 certified; macOS tested		
	Mac® Resolution (min): CONNECTOR	2560x1440		
	USB 3.2 Type A Down Stream:	2		VG2756-2K x1, 3-pin Plug (IEC C13 /
	USB 3.2 Type B Up Stream:	1	PACKAGE CONTENTS:	CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB Type-C Cable
	USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (90W power charger)		(Male-Male) x1, USB Å/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
	HDMI 1.4:	1	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
	DisplayPort:	1	Manage to a	*Warranty offered may differ from
	DisplayPort Out:	1	Warranty:	market to market
	Power in:	3-pin Socket (IEC C14 / CEE22)	Power Management:	Energy Star standards, EPEAT
	Ethernet LAN (RJ45):	1		
	AUDIO			
	Internal Speakers:	2Watts x2		
	POWER			
	Eco Mode (Conserve):	16.81W		
	Eco Mode (optimized):	21.12W		
	Consumption (typical):	26.35W		
	Consumption (max):	35.94W		
	Voltage:	AC 100-240V		
	Stand-by:	0.5W		
	Power Supply:	Internal Power Supply		
	ADDITIONAL HARDWARE			
	Kensington Lock Slot:	1		
	Cable Organization:	Yes		
	CONTROLS	Kou 1 (ouo) Kou 0 Kou 0 Kou 1		
	Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust,		
	On Screen Display:	ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
	OPERATING CONDITIONS			
	Temperature:	32°F to 104°F (0°C to 40°C)		
		×		
Wir kennen	Ihre Datenschutzpräferenze	en noch nicht.		
	Datenschutz einstellen			
		yrıght © ViewSonic Corpor	ation 2000-2022. All rights reserved.	