Eaton 9PX3000RT

Catalog Number: 9PX3000RT

Eaton 9PX UPS, 2U, 3000 VA, 2700 W, L5-30P input, Outputs: (6) 5-20R, (1) L5-30R, 120V

General specifications

Product Name

Eaton 9PX UPS

UPC

743172081285

Product Height

3.4 in

Product Weight

63.1 lb

Catalog Number

9PX3000RT

Product Length/Depth

23.8 in

Product Width

17.3 in

Compliances

IEC 62040-2 Cat C1 CISPR22 Class B FCC part 15 Class B VCCI Class B CE Marked

Photo is representative

Certifications

cULus Listed

NOM

ENERGY STAR certified



Battery

Runtime graph

View runtime graph

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

Battery type

Sealed, lead-acid

Extended battery capability

Add up to 4 extended battery modules (EBM). Part number 9PXEBM72RT

Electrical output

Receptacle

(6) 5-20R, (1) L5-30R

Topology

Online/Double-conversion

Wattage

2700 W

VA rating

3000 VA

Output waveform

True sine wave

Voltage

120V

Output power factor

0.9

Output nominal voltage

120V default (100/110/120/125V)

Output voltage range

±1% steady-state

Output frequency

50/60 Hz

Electrical input

Input connection

L5-30P

Input cord length

8 ft

Input nominal voltage

120V default (100/110/120/125V)

Input frequency range

60 Hz: 50-70 Hz, 50 Hz: 40-60 Hz

Input power factor

>0.99 typical

Communications

Communication

MiniSlot + 1 USB port + 1 serial RS232 port + 1 mini-terminal block for remote ON/OFF + 1 mini-terminal block for remote power off + 1 mini-terminal block for output relay Communication slot

Expansion slots

(1) Mini-Slot (MS) expansion port. The following optional connectivity cards may be ordered separately.
Gigabit Network Card part

number: NETWORK-M2 Modbus card part number:

INDGW-M2

Relay card part number:

RELAY-MS

Software compatibility

Intelligent Power Software Suite

User interface

Graphical display, 5-button programmable menu

Environmental

Altitude

0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)

BTU Rating

Online: 844, Battery: 1462

Noise level

<47 dB at 1 meter

Relative humidity

0-96% non-condensing

Temperature range

0° to 40°C (32° to 104°F)

Additional specifications

Form factor

Rack/tower

Rack size

2U

Rack mounting kit

Yes

Efficiency

91%

Package contents

9PX3000RT UPS

4-post rail kit

Safety manual

User manual

Tower pedestals

RS-232 serial cable

USB cable

Intelligent Power Software

Suite CD

Internal bypass

Yes

Warranty and support

Standard factory warranty

3-YEAR FACTORY

WARRANTY

- 3 years
- Parts, electronics and batteries coverage
- Standard ground shipping
- Technical support

Extended service plans

ADVANCED DEPOT

EXCHANGE

- 5-year depot repair:

9SW5Y-3000UC

- Expedited parts coverage

for 5 years

- Parts, electronics and UPS

batteries coverage

- Next business day

shipping

- Technical support

5-YEAR ON-SITE PLAN:

WFLN75XX-6009UC

- On-site parts and labor
- coverage for years 5
- Parts, electronics and UPS

batteries coverage

- 24x7 on-site labor

coverage, next-day response

- Next-day shipping
- Technical support

Resources

Brochures

Eaton UPS and battery services - EN

Eaton UPS Services Quick Guide - EN

Eaton 9PX 700-3000 VA UPS brochure

Drawings

Eaton 9PX UPS 2000-3000 VA 120V outline drawing

Eaton 9PX UPS 9PX3000RT technical drawing

Battery Integration System Pro-E drawing

Manuals and user guides

9PX 700-3000 VA 2U UPS user guide

9PX 2-post rack kit user guide

9PX battery integration system user guide

Specifications and datasheets

9PX 700-3000 VA UPS technical specification

Eaton 9PX UPS guide specification: 700-3000 VA

Eaton Specification Sheet - 9PX3000RT



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia